



Pickup Van

Technical Specifications	
Engine	
Туре	Single Cylinder, Four Stroke, Diesel Displacement 435 CC
Maximum Power	7.40 KW @3600 rpm
Fuel Consumption	35 <u>+</u> 3 km/ltr
Compression Ratio	19:1 (+/- 0.5%)
Maximum Speed	55 kmph
Starting	Electric, Self Start
Cooling	Forced Air Cooled
Transmission	
Clutch Type	MultiPlate Wet Type
Gear Type	Constant mesh type
Gear Box	4 Forward and 1 Reverse
Maximum Gradeability	7°
Suspension	
• Front	Helical Spring with hydraulic Shock absorber.'
• Rear	Rubber Compression Spring & hydraulic Telescopic Shock absorber.

LOVSON

98, Bajaj Bhavan, Nariman Point, Mumbai – 400 021. India Tel.- +91-22-66359898 Fax - +91-22-22040517

E-mail: sales@lovson.net Website: www.auto-rickshaw.com



Brake	
Service brake (Brief description)	Hydraulic
ABS Fitted (Yes / No / Optional)	No
Front (Disc / Drum)	Drum
Rear (Disc / Drum)	Drum
Total braking area, cm ²	226.5 cm ²
Parking brake	Operated by right hand
Secondary brake	N.A.
Wheels and Tyres	
Wheel rim size	3.0 x 10
Tyre size designation including ply rating load index / speed rating	4.50 x 10, 8 ply
Tyre Type (Radial/Cross/Tube/Tubeless)	Cross Type
Laden Tyre pressure	Front: 3.25 Kg/Cm ²
(front & rear), kg/cm2	Rear: 3.5 Kg/Cm ²
Electrical system	
System voltage, V	12 V DC
Battery rating, Ah	50 Ah
Wiper motor	Power Operated
Wiping system (Brief description)	12 V, Power Operated DC Motor
Fuel tank	
Material	Metallic
Capacity, I	10 Liters

In our constant endeavour to improve the product, the specifications are subject to change without any prior notice.

LOVSON